



430 US HWY 62/180 West, Seminole, TX 79360
 Phone 432.758.9900 • Fax 432.758.9903
 Email sales@jnlsteel.com

BUILD IT WITH STEEL

BUILD IT TO LAST



			
POLAR WHITE* SR .60 • SRI 71	LIGHT STONE* SR .50 • SRI 57	ASH GRAY* SR .48 • SRI 55	SADDLE TAN* SR .48 • SRI 55
			
COCOA BROWN* SR .28 • SRI 27	RUSTIC RED* SR .36 • SRI 38	EVERGREEN* SR .31 • SRI 31	CHARCOAL GRAY SR .27 • SRI 26
			
HAWAIIAN BLUE SR .25 • SRI 24	BURNISHED SLATE SR .28 • SRI 27	OLD TOWN GRAY SR .42 • SRI 47	FERN GREEN SR .27 • SRI 26
			
IVORY SR .60 • SRI 71	BERRY SR .30 • SRI 18	DESERT SAND SR .42 • SRI 47	CRIMSON RED SR .38 • SRI 42
			
GALVALUME	COPPER METALLIC SR .45 • SRI 50	GALLERY BLUE SR .27 • SRI 27	BLACK SR .30 • SRI 29
			
	COLONY GREEN SR .32 • SRI 31	LIGHT BROWN SR .31 • SRI 31	

- Final color selection should be made from actual color chips.
- A 40-year limited paint warranty is available for all colors upon request. Please inquire about other warranties available, like 25 or 10-year.
- Solar Reflectivity (SR):
Solar reflectivity or reflectance is the measure of a material's ability to reflect solar energy or sunlight from its surface. SR values are numbered 0 to 1.0. A value of 0 indicates that the surface absorbs all solar energy and a value of 1.0 indicates total reflectance. ENERGY STAR requires an SR value of 0.25 or higher for steep slope roofing (above 2:12) and an SR value of 0.65 or higher for low slope roofing (2:12 or less). For more information, please visit www.energystar.gov.
- Solar Reflectance Index (SRI):
The SRI is used to determine compliance with LEED requirements and is calculated according to ASTM E 1980 using values for reflectance and emissivity. To meet LEED requirements, a roofing material must have an SRI of 29 or greater for steep slope roofing and an SRI value of 78 or higher for low slope roofing. For more information, visit www.usgbc.org.

Due to variations in computer monitors, we cannot guarantee the accuracy of colors presented on-screen with actual products. Please refer to a color card or paint swatches to ensure color accuracy.

*Available in Purlin Bearing Leg.



Sheet Metal Profiles

- 1 R-Panel or PBR-Panel**
- 2 AG-Panel**
- 3 Pro-Rib**
- 4 U-Panel or PBU-Panel**

Standing Seam Profiles

- -
 -
 -
- 5** SSQ100 Mech. Seamed 1"
6 SSQ210A ARMCO Style 2"
7 SSQ675 1-3/4" Snap Lock
8 FFQ100 1" Fastener Flange
 SSQ100 Mech. Seamed 1-1/2"
 SSQ100 Mech. Seamed 2"

Commercial Trim

- 9 Peak Sheet**
- 10 Sculptured Post Hung Gutter**
- 11 Sculptured Pre Hung Gutter**
- 12 Sculptured Rake**
- 13 Outside Corner**
- 14 Inside Corner**
- 15 Sculptured High Side Eave**
- 16 Long Eave Trim**
- 17 Head Trim**
- 18 Jamb Trim**
- 19 Base Trim**
- 20 Sidewall Transition**

Residential Trim

- 21 Sculptured Ridge**
- 22 Short Eave Trim**

* 3"R 2"U
- 23 Residential Rake**

* 4"R 3"U
- 24 Valley**

Custom Trim Available